

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 October 2002 (24.10.2002)

PCT

(10) International Publication Number
WO 02/083208 A2

(51) International Patent Classification⁷: A61M 5/142

(21) International Application Number: PCT/US01/44438

(22) International Filing Date:
27 November 2001 (27.11.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/282,775 10 April 2001 (10.04.2001) US

(71) Applicant: MEDTRONIC, INC. [US/US]; 710
Medtronic Parkway NE, Minneapolis, MN 55432 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report*

(72) Inventor: OLSEN, James, M.; 10380 51st Place North, Plymouth, MN 55442 (US).

(74) Agents: WALDKOETTER, Eric, R. et al.; Medtronic, Inc. LC340, 710 Medtronic Parkway NE, Minneapolis, MN 55432 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



(54) Title: PERMANENT MAGNET SOLENOID PUMP FOR AN IMPLANTABLE THERAPEUTIC SUBSTANCE DELIVERY DEVICE

WO 02/083208 A2

(57) Abstract: A medical device known as an implantable therapeutic substance delivery device is configured for implanting in humans to deliver a therapeutic substance such as pharmaceutical compositions, genetic materials, and biologics to treat a variety of medical conditions such as pain, spasticity, cancer, and many other conditions. The therapeutic substance delivery device has a permanent magnet solenoid pump that is energy efficient, accurate, small, compatible with therapeutic substances, and has many other improvements. The implantable therapeutic substance delivery device has a housing, a therapeutic substance reservoir, a power source, electronics, and a permanent magnet solenoid pump. The therapeutic substance reservoir is configured to contain a therapeutic substance and is coupled to the housing. The power source is carried in the housing to power the electronics and solenoid pump. The electronics are coupled to the solenoid pump and the solenoid pump is coupled to the therapeutic substance reservoir. The permanent magnet solenoid pump is configured for pumping therapeutic substance from the therapeutic substance reservoir through an infusion outlet at a programmed infusion rate. Many embodiments of the permanent magnet solenoid pump and its methods of operation are possible.

**PERMANENT MAGNET SOLENOID PUMP FOR AN IMPLANTABLE
THERAPEUTIC SUBSTANCE DELIVERY DEVICE**

5

BACKGROUND OF THE INVENTION

This disclosure relates to a medical device and more particularly to an implantable therapeutic substance delivery device with a piston operated pump.

10 The medical device industry produces a wide variety of electronic and mechanical devices for treating patient medical conditions such as pacemakers, defibrulators, neurostimulators, and therapeutic substance delivery pumps. Medical devices can be configured to be surgically implanted or connected externally to the patient receiving treatment. Clinicians use medical devices alone or in combination with therapeutic substance therapies and surgery to treat patient medical conditions. For some medical conditions, medical devices provide the best, and sometimes the only, therapy to restore an individual to a more healthful condition and a fuller life. Implantable drug delivery pumps can be used to treat conditions such as pain, spasticity, cancer, and a wide variety of other medical conditions.

15 An implantable drug delivery pump is implanted by a clinician into a patient at a location appropriate for the therapy that interferes as little as practicable with patient activity such as subcutaneous in the lower abdomen. Typically, a drug delivery catheter is connected to the drug pump outlet and implanted to infuse the drug, infusate or other therapeutic substance at a programmed infusion rate and predetermined location to treat the medical condition. Reliable and accurate operation of the drug pump is important because both inadequate and unintended therapeutic substance delivery can create patient complications. Many drug pumps are configured, so the pump can be replenished with drug through a refill port or septum while the pump is implanted, so the period the pump can be implanted may not be limited by drug capacity. In electrically powered implantable drug pumps, the period the pump can be implanted is often limited by factors such as battery consumption, corrosive damage, and mechanical wear. The relative large size of some implantable drug pumps can limit locations where the device can be implanted in a patient. An example of an implantable drug pump is shown in Medtronic, Inc.

20

25

30

"SynchroMed® Infusion System" Product Brochure (1995). Implantable drug pumps can use a variety of pumping mechanism such as a piston pump, rotary vane pump, osmotic pump, Micro Electro Mechanical Systems (MEMS) pump, diaphragm pump, peristaltic pump, and solenoid piston pump to infuse a drug into a patient.

5 Peristaltic pumps typically operate by a battery powered electric motor that drives peristaltic rollers over a flexible tube having one end coupled to a therapeutic substance reservoir and the other end coupled to an infusion outlet to pump the therapeutic substance from the therapeutic substance reservoir through the infusion outlet. An implantable peristaltic pump typically consumes energy at about 6 Joules per milliliter (J/ml) of fluid
10 pumped. Peristaltic pumps are typically about 3% efficient in terms of electrical energy input and fluid work output. In an implantable therapeutic substance delivery device having a peristaltic pump, the peristaltic pump is typically one of the largest components in the device and can consume 90% or more of the available battery power. The flexible tube used in a peristaltic pump is typically permeable to some therapeutic substance
15 components such as water that can then infiltrate into the hermetically sealed housing and cause corrosion. Additionally, the flexible tube can expand resulting in decreased accuracy.

Solenoid piston pumps such as variable reluctance solenoid pumps and permanent magnet solenoid pumps can have disadvantages compared to peristaltic pumps such as
20 higher energy consumption, difficulty with passing air, difficulty with valve sealing, and therapeutic substance material compatibility. Energy consumption of a reluctance solenoid pump can be relatively high because of pump construction and nonlinear piston force. Reluctance solenoid pumps can be constructed with a large pole piece that can cause fluid energy loss. Reluctance solenoid pump nonlinear piston force caused when
25 piston force increases as the poles close the gap can also reduce pumping efficiency. Passing air can be difficult for solenoid pumps because of large dead volumes created by valve geometries. Sealing valves can be difficult because passively operated valves can unintentionally open under some circumstances creating safety concerns. Therapeutic substance material compatibility can be difficult to achieve in some solenoid pumps
30 because of the pumping components that are in contact with the therapeutic substance. Examples of previous solenoid pumps are shown in U.S. Patent No. 4,883,467

“Reciprocating Pump For An Implantable Medication Dosage Device” by Franetzki et al. (November 28, 1989) and U.S. Patent No. 4,569,641 “Low Power Electromagnetic Pump” by Falk et al. (February 11, 1986). An example of a permanent magnet pump configured for pumping liquids such as water or kerosene is shown in U.S. Patent No. 5,472,323
5 “Moveable Magnet Type Pump” by Hirabayashi et al. (December 5, 1995).

For the foregoing reasons, there is a need for a permanent magnet pump for an implantable therapeutic substance delivery device that is energy efficient, small, compatible with therapeutic substances, and has many other improvements.

SUMMARY OF THE INVENTION

10 A permanent magnet solenoid pump for an implantable therapeutic substance delivery device embodiment is energy efficient, accurate, small, compatible with therapeutic substances, and has many other improvements. The permanent magnet solenoid pump is coupled to electronics and coupled to a therapeutic substance reservoir outlet to pump therapeutic substance from the therapeutic substance reservoir through an
15 infusion outlet at a programmed rate. The permanent magnet solenoid pump is carried in a therapeutic substance delivery device that has a housing, a therapeutic substance reservoir coupled to the housing, a power source carried in the housing, and electronics carried in the housing and coupled to the power source. Many embodiments of the permanent magnet solenoid pump and its methods of operation are possible.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows the environment of an implantable therapeutic substance delivery device
embodiment;

FIG. 2 shows an implantable therapeutic substance delivery device with catheter
25 embodiment;

FIG. 3 shows an implantable therapeutic substance delivery device embodiment;

FIG. 4 shows the implantable therapeutic substance delivery device of FIG. 3 with a
portion of a housing removed;

FIG. 5 shows another implantable therapeutic substance delivery device embodiment
30 having a separate therapeutic substance reservoir;

FIG. 6 shows the implantable therapeutic substance delivery device of FIG. 5 with a portion of a housing removed;

FIG. 7 shows a permanent magnet solenoid pump embodiment;

FIG. 8 shows an exploded view of the permanent magnet solenoid pump of FIG. 7 embodiment;

FIG. 9 shows an exploded view of a pump piston for a permanent magnet solenoid pump three-coil embodiment;

FIG. 10 shows an isometric cross-section view of a pump piston for a permanent magnet solenoid pump three-coil embodiment;

FIG. 11 shows a cross section view of a pump piston for a permanent magnet solenoid pump three-coil embodiment;

FIG. 12 shows an isometric cross-section view of a permanent magnet solenoid pump two-coil embodiment;

FIG. 13 shows a cross section view of a permanent magnet solenoid pump two-coil embodiment;

FIGS. 14a and 14b show a pump piston with an alternative piston fluid path embodiments;

FIG. 15 shows an outlet valve embodiment;

FIG. 16 shows a schematic of a two-coil permanent magnet solenoid pump embodiment;

FIG. 17 shows a schematic of a two-coil with permanent magnet pole pieces permanent magnet solenoid pump embodiment;

FIG. 18 shows a schematic of a three-coil permanent magnet solenoid pump embodiment;

FIG. 19 shows a schematic of a three-coil with permanent magnet pole pieces permanent magnet solenoid pump embodiment; and,

FIG. 20 shows a flow diagram of a method for operating a permanent magnet solenoid therapeutic substance delivery device embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 shows the environment of an implantable medical device known as an implantable therapeutic substance delivery device 30, also known as a drug pump, having a permanent magnet solenoid pump embodiment. The therapeutic substance delivery device 30 can be used for a wide variety of therapies such as pain, spasticity, cancer, and many other medical conditions. The implantable therapeutic substance delivery device 30

is typically implanted by a clinician such as a surgeon in a sterile surgical procedure performed under local, regional, or general anesthesia. Before implanting the therapeutic substance delivery device 30, a catheter 32 is typically implanted with the distal end position at the desired therapeutic substance delivery site 34 and the proximal end tunneled to the location where the therapeutic substance delivery device 30 is to be implanted. The catheter 32 and the therapeutic substance delivery site 34 can generate a back pressure during infusion known as the infusion site pressure that the therapeutic substance delivery device 30 overcomes to deliver therapeutic substance 36 at the infusion site. The implantable therapeutic substance delivery device 30 is generally implanted subcutaneously about 2.5 cm (1.0 inch) beneath the skin where there is sufficient subcutaneous tissue to support the implanted system. Once the therapeutic substance delivery device 30 is subcutaneously implanted into the patient, the incision can be sutured closed and the therapeutic substance delivery device 30 can begin operation.

The therapeutic substance delivery device 30 operates to infuse a therapeutic substance 36 at a programmed rate into a patient 38. The therapeutic substance 36 is a product or substance intended to have a therapeutic effect such as pharmaceutical compositions, genetic materials, biologics, and other substances. Pharmaceutical compositions are chemical formulations intended to have a therapeutic effect such as intrathecal antispasmodics, pain medications, chemotherapeutic agents, and the like. Pharmaceutical compositions are often configured to function in an implanted environment with characteristics such as stability at body temperature to retain therapeutic qualities, concentration to reduce the frequency of replenishment, and the like. Genetic materials are substances intended to have a direct or indirect genetic therapeutic effect such as genetic vectors, genetic regulator elements, genetic structural elements, DNA, and the like. Biologics are substances that are living matter or derived from living matter intended to have a therapeutic effect such as stem cells, platelets, hormones, biologically produced chemicals, and the like. Other substances are substances intended to have a therapeutic effect yet are not easily classified such as saline solution, fluoroscopy agents, and the like.

The therapeutic substance 36 can be replenished in some embodiments of the implanted therapeutic substance delivery device 30 by inserting a non-coring needle

connected to a syringe filled with therapeutic substance 36 through the patient's skin into a septum 40 on the therapeutic substance delivery device 30 to fill the implanted device. If the therapeutic substance delivery device 30 requires replacement due to conditions such as battery depletion or other condition, an incision is made near the implanted therapeutic substance delivery device 30, and the old therapeutic substance delivery device 30 is removed, also known as explanted. After the old therapeutic substance delivery device 30 has been explanted, typically a new therapeutic substance delivery device 30 is then implanted.

FIGS. 3-6 show views of therapeutic substance delivery device 30 embodiments. An implantable therapeutic substance delivery device 30 with a permanent magnet solenoid pump comprises a housing 41, a therapeutic substance reservoir 42, a power source 44, electronics 46, and a permanent magnet solenoid pump 48. Typically, the therapeutic substance delivery device 30 components are carried in a single housing 41, such as shown in FIGS. 3 and 4, that is manufactured from a material that is biocompatible and hermetically sealed such as titanium, tantalum, stainless steel, plastic, ceramic, and the like. Therapeutic substance delivery device 30 components can also be placed in more than one housing 41, such as shown in FIGS. 5 and 6, that are appropriately coupled. The therapeutic substance reservoir 42 can be placed inside the housing 41 or can be separated from the housing 41 with a fluid coupling such as a tube between the reservoir 41 and the housing 41. The therapeutic substance reservoir 42 is configured to contain a therapeutic substance 36 and may use geometries such as a metal bellows, polyomeric bag, and the like. The therapeutic substance reservoir 42 has a reservoir outlet 52 and can have a septum 40 for refilling the reservoir 42.

The power source 44 is carried in the housing 41. The power source 44 is selected to operate the solenoid pump 48 and electronics 46 such as a lithium ion (Li+) battery, capacitor, and the like. The electronics 46 are coupled to the power source 44 and typically include memory and a controller. The controller can be an Application Specific Integrated Circuit (ASIC) state machine, a gate array, or may include a microprocessor. The electronics 46 are configured to control the solenoid pump 48 infusion rate and can be configured to operate many other features such as patient alarms and the like. The electronics 46 can also include telemetry circuitry configured to receive and send

information when the therapeutic substance delivery device 30 is implanted to allow programming of the infusion rate. The solenoid pump 48 is coupled to the electronics 46 and coupled to the therapeutic substance reservoir outlet 52 and configured for pumping therapeutic substance 36 from the therapeutic substance reservoir 42 through an infusion outlet 54 at a programmed rate.

FIGS 7-11 show a three coil embodiment of the solenoid pump. The permanent magnet solenoid pump 48 comprises a pump cylinder 56, a pump piston 58, a biasing element 60, an inlet valve 62, an outlet valve 64, a permanent magnet 66, a first coil 68, and a second coil 70. The solenoid pump 48 is coupled to the electronics 46, the therapeutic substance reservoir outlet 52, and the infusion outlet 54. The solenoid pump 48 is configured for pumping therapeutic substance 36 from the reservoir 42 through an infusion outlet 54 at a programmed rate.

The pump cylinder 56 has an inlet enclosure 72, an outlet enclosure 74, a therapeutic substance inlet 76, and an infusion outlet 54. The inlet enclosure 72 transitions the pump cylinder 56 to the therapeutic substance inlet 76. The outlet enclosure 74 transitions the pump cylinder 56 to the infusion outlet 54. The therapeutic substance inlet 76 is coupled to a therapeutic substance reservoir outlet 52 and coupled to the inlet enclosure 72 on the pump cylinder 56. Some embodiments can include a piston seal 78 positioned between the pump cylinder 56 and the pump piston 58 to reduce therapeutic substance 36 flow between the pump piston 58 and the pump cylinder 56 and provide other functions. The piston seal 78 can be configured to serve as a guide for the biasing element 60 and to cushion the pump piston 58 at the end of pump piston 58 retraction for the intake stroke. The piston seal 78 is manufactured from a resilient material with good sealing qualities such as synthetic rubber, PTFE, silicone, and the like.

The pump piston 58 is moveable within the pump cylinder 56 and has a piston inlet end 80, a piston outlet end 82, and a piston fluid path 84. The pump piston 58 forms an inlet chamber 86 between the pump piston 58 and the inlet enclosure 72 and a pumping chamber 88 between the pump piston 58 and the outlet enclosure 74. The inlet chamber 86 contains the therapeutic substance 36 that is displaced when the pump piston 58 retracts. The pumping chamber 88 contains the therapeutic substance 36 that is displaced when the pump piston 58 is actuated. The piston fluid path 84 is configured to provide

fluid communication between the inlet chamber 86 and the pumping chamber 88 that is controlled by the inlet valve 62. The piston fluid path 84 can take a wide variety of forms such as a central fluid path, a side fluid path, a partial central and partial side fluid path, and the like.

5 The biasing element 60 is positioned in the pump cylinder inlet chamber 86 between the pump piston 58 and the inlet enclosure 72. The biasing element 60 exerts force on the pump piston 58 to expulse therapeutic substance 36 through the infusion outlet 54. In some embodiments, the biasing element 60 exerts substantially the sole force on the pump piston 58 to expulse therapeutic substance 36 through the infusion outlet 54.
10 The biasing element 60 also provides force to maintain the pump piston 58 in an actuated position until retracted to seal the inlet valve 62 against the outlet enclosure 74 to provide redundant protection against unintended flow of therapeutic substance 36 to the patient 38. The biasing element 60 can be one or more of a wide variety of biasing structures that are selected to provide the desired biasing force on the pump piston 58. The desired force of
15 the biasing element 60 in a particular embodiment is the force required to overcome any frictional losses during the pump piston 58 expulsion stroke, to generate pressure to open the outlet valve 64, and to overcome pressure losses between the infusion outlet 54 and the infusion site 34 that can be located at the distal end of the catheter 32. Some specific embodiments of the biasing element 60 include a spring, a coil spring, and the like.

20 The inlet valve 62 is carried on the pump piston outlet end 82. The inlet valve 62 can be a variety of inlet valves 62 such as a flapper valve, annular flapper valve, ball valve, reed valve, duckbill valve, poppet valve, and the like. The outlet valve 64 is carried in the outlet enclosure 74 and coupled to the infusion outlet 54. The outlet valve 64 improves solenoid pump 48 safety by substantially preventing unintended flow of therapeutic
25 substance 36 when the reservoir 42 pressure is greater than the infusion site 34 pressure. The outlet valve 64 improves solenoid pump 48 accuracy by maintaining sufficient back pressure to keep the inlet valve 62 closed during therapeutic substance 36 expulsion through the infusion outlet 54 so that addition therapeutic substance 36 is not infused when the reservoir 42 pressure is greater than the infusion site 34 pressure. The outlet valve 64
30 can be a variety of outlet valves 64 such as a flapper valve, ball valve, reed valve, duckbill valve, poppet valve, and the like. An outlet valve embodiment is shown in FIG. 15.

Some embodiments of the solenoid pump 48 can include an anti-cavitation valve 90 position in fluid communication with the therapeutic substance inlet 76. The anti-cavitation valve 90 substantially prevents therapeutic substance 36 in the inlet chamber 86 from flowing back through the therapeutic substance inlet 76 during pump piston 58 retraction. Since the therapeutic substance 36 cannot flow backwards, pressure in the inlet chamber 86 increases as the pump piston 58 retracts causing the therapeutic substance 36 to flow through the piston fluid path 84 without causing the pump chamber 88 pressure to drop low enough to cause dissolved gasses to come out of solution. Also by substantially preventing the back flow of therapeutic substance 36 through the therapeutic substance inlet 76 during pump piston 58 retraction, piston pump 58 efficiency is improved because wasted therapeutic substance 36 flow is minimized. The anti-cavitation valve 90 can be a wide variety of anti-cavitation valves 90 such as a flapper valve, annual flapper valve, ball valve, reed valve, duckbill valve, poppet valve, and the like. In addition to displacing therapeutic substance 36 that operates the inlet valve 62, outlet valve 64, and anti-cavitation valve 90, the pump piston 58 carries a permanent magnet 66.

The permanent magnet 66 is at least a first permanent magnet 66 having a first pole 92 and a second pole 94. The permanent magnet 66 is carried by the pump piston 58 and acted on by the magnetic fields created by the coils 67 that include at least the first coil 68 and at least the second coil 70. When the first coil 68 and second coil 70 are energized, the coils 67 produce an electromagnetic axial force that acts on the permanent magnet 66 to impart motion to the pump piston 58. In some embodiments, there can be more than one permanent magnet 66 such as a first permanent magnet 66, a second permanent magnet 96, a third permanent magnet 98 and so forth. Also in some embodiments, there can be more than a first coil 68 and second coil 70 such as a third coil 71 and so fourth. When using more than one permanent magnet 66, like poles are positioned adjacent to one another, and there are $N - 1$ operational permanent magnets 66 where N is the number of coils 67 in the range from about 3 to 10. The permanent magnet 66 is manufactured from a hard ferromagnetic material such as samarium cobalt, neodymium, ceramic, alnico, and the like. Since the permanent magnet 66 material is typically not therapeutic substance compatible or biocompatible, the permanent magnet 66 is typically isolated from the therapeutic substance 36 by the piston fluid path 84 and the pump piston 58 sealed is by

the piston inlet end 80 and piston outlet end 82. Positioned in operating relationship to the permanent magnet 66 are the first coil 68 and the second coil 70. An alternative solenoid pump 48 embodiment using two coils 67 is shown in FIGS. 12-13.

FIGS. 16-19 show block diagram of some of the permanent magnet solenoid pump 48 permanent magnet 66 and coil 67 embodiments. There is at least a first coil 68 configured around the pump cylinder 56 positioned adjacent to the first pole 92 of the permanent magnet 66, and at least a second coil 70 configured around the pump cylinder 56 positioned adjacent to the second pole 94 of the permanent magnet 66. The first coil 68 and the second coil 70 can be reversed in relation to the permanent magnet 66, so the first coil 68 is adjacent to the second pole 94 and the second coil 70 is adjacent to the first pole 92. Other embodiments of the permanent magnet solenoid pump 48 can have more than a first coil 68 and second coil 70 such as a third coil 71 or N operational coils where N is an integer in the range from about 3 to 10. When the solenoid pump 48 is configured with N coils there will be $N - 1$ operational permanent magnets 66. The following discussion will use the term coil 67 to refer a first coil 68 and a second coil 70, or N coils and permanent magnet 66 to refer to a first permanent magnet 66 or $N - 1$ permanent magnets.

The coils 67 are typically wound in opposite directions, so current flows in opposite directions to generate opposing magnetic fields. Alternatively, the coils 67 can be wound in the same direction and the voltage polarity applied to the coils 67 can be opposing to cause current to flow in opposite directions to generate opposing magnetic fields. The coils 67 are configured to create a force in one direction for one permanent magnet pole 92 and in the same direction for the other permanent magnet pole 94. The coils 67 are energized for pump piston 58 retraction toward the inlet enclosure 72 to fill the pump chamber 88 from the inlet chamber 86. Since the coils 67 are not typically compatible with therapeutic substances or biocompatible, the coils 67 are typically isolated from the therapeutic substance 36 by the pump cylinder 56 and isolated from the patient 38 by the housing 41. The pump cylinder 56 is manufactured from any therapeutic substance compatible material that meets design requirements such as titanium, tantalum, stainless steel, plastic, ceramic, and the like. The permanent magnet 66 and coils 67 can be inserted into the pump cylinder 56 along with the pump piston 58 and then the inlet enclosure 72

and outlet enclosures 74 can be welded to isolate the permanent magnet 66 and coils 67 from the therapeutic substance 36. The coil's 67 electromagnetic axial force can be enhanced with a magnetically permeable yoke 100 and pole pieces 102.

5 The magnetically permeable yoke 100 and pole pieces 102, although not required for operation, enhance the electromagnetic axial force created by the coils 67. The magnetically permeable yoke 100 is placed around the coils 67 to improve magnetic efficiency. The magnetically permeable yoke 100 also shields the permanent magnet 66 from external high magnetic fields, until the magnetically permeable yoke 100 becomes saturated, to protect the permanent magnet 66 from demagnetization. The external high
10 magnetic field can be created by equipment such as Magnetic Resonance Imaging (MRI) equipment, magnetic security equipment, and the like. The pole pieces 102 can be positioned adjacent to one or more of the permanent magnet's 66 poles. For example, a first pole piece 104 can be carried on the pump piston 58 between the permanent magnet 66 and the inlet enclosure 72 to improve magnetic coupling. A second pole piece 106 can
15 be carried on the pump piston 58 between the permanent magnet 66 and the outlet enclosure 74 to improve magnetic coupling.

When the pump piston 58 is fully positioned toward the inlet enclosure 72, the maximum pump chamber 88 volume is created. The pump chamber 88 has a pump chamber 88 volume comprising a stroke volume and a dead volume. The stroke volume is
20 in the range from about 0.5 micro liters to about 5.0 micro liters. The sum of an inlet valve 62 opening pressure and the outlet valve 64 opening pressure exceeds the maximum pressure of the reservoir 42 less the infusion site 34 pressure to substantially prevent free flow of therapeutic substance 36 to the patient 38. The dead volume is less than half the stroke volume in the range from about 0.25 micro liters to about 2.5 micro liters. The
25 solenoid pump's 48 small dead volume compared to the stroke volume improves the solenoid pump's 48 capability to pass air because of the low vacuum pressure that is typically generated in the pump chamber 88. The inlet valve 62 and outlet valve 64 opening pressures are selected to prevent unintended infusion under extreme operating conditions. Unintended infusion is substantially prevented by selecting the inlet valve 62
30 opening pressure and the outlet valve 64 opening pressure so the sum of these pressures is greater than the maximum pressure difference between the reservoir 42 and the infusion

site 34. For example, unintended infusion is prevented when the reservoir 42 pressure is high and the ambient pressure (typically the same as the infusion site 34 pressure) is low that can occur when the reservoir 42 is full and the patient 38 is exposed to high temperature at high altitude.

The solenoid pump's 48 ability to pass air and operate accurately is a function of the solenoid pump's 48 compression ratio, the reservoir outlet 52 pressure, the infusion outlet 54 pressure, and outlet valve 64 cracking (opening) pressure. For adiabatic systems with ideal gases, the compression ratio in the pump chamber 88 can be expressed as $CR_{pc} = \frac{V_{pc\ final}}{V_{pc\ initial}}$ (Equation 1) where CR_{pc} is the compression ratio in the pump chamber 88,

$V_{pc\ final}$ is the final volume in the pump chamber 88 calculated by

(*stroke volume + pump chamber dead volume*) where

stroke volume = *piston area* × *piston stroke*, and $V_{pc\ initial}$ is the initial volume in the pump chamber 88 also known as the *pump chamber dead volume* which is also the pump chamber volume remaining after the pump piston 58 has expelled the stroke volume. The

compression ratio in the inlet chamber 86 can be expressed as $CR_{ic} = \frac{V_{ic\ final}}{V_{ic\ initial}}$ (Equation 2)

where CR_{ic} is the compression ratio in the inlet chamber 86 and V_{ic} is the volume in the inlet chamber 86, $V_{ic\ final} = (\text{stroke volume} + \text{inlet chamber dead volume})$, and

$V_{ic\ initial} = (\text{inlet chamber dead volume})$. From these relationships, it is apparent that pump chamber 88 pressure will be decreasing and inlet chamber 86 pressure will be increasing as the pump piston 58 retracts. For therapeutic substance 36 to flow into the pump chamber 88 when gas bubbles are present, the pressure in the pump chamber 88 during the pump piston 58 stroke must drop substantially below the inlet chamber 86 pressure. For therapeutic substance 36 to flow out of the pump chamber 88, the expulsion pressure must be greater than the infusion outlet 54 pressure. Therapeutic substance 36 flows through the outlet valve 64 when $P_{pc} \geq P_a + P_{ovc}$, where P_{pc} is the pressure in the pump chamber 88, P_a is the ambient pressure at the infusion outlet 54, and P_{ovc} is outlet valve 64 cracking

(opening) pressure. By selecting the appropriate outlet valve 64 cracking pressure the risk of unintentional infusion can be substantially eliminated.

The permanent magnet solenoid pump 48 is designed to be energy efficient consuming less than about 3.0 Joules per milliliter (J/ml) at about 137,895 pascals (20 pounds/square inch) back pressure. The solenoid pump 48 is about 5% to 10% efficient in terms of electrical energy input and fluid work output. The energy efficiency of the solenoid pump 48 to a large degree determines energy efficiency of the implantable therapeutic substance delivery device 30 and the size of power source 44 needed. For example, doubling solenoid pump 48 efficiency can theoretically result in nearly a 50% reduction in energy consumption and a 50% reduction in power source 44 size. Additionally, the solenoid pump 48 can be a wide variety of sizes. The design of the solenoid pump 48 permits small sized configuration such as less than about 20.0 mm long by about 6.0 mm in diameter with a total volume less than about 0.5 cc. The small size of the solenoid pump 48 also permit having a small implantable therapeutic substance delivery device 30 that can be implanted in a wide variety of location such as the head, arms, and legs.

Operation

FIG. 20 shows a flowchart of a method for operating an implantable therapeutic substance delivery device 30 having a permanent magnet solenoid pump 48 embodiment. Generally, therapeutic substance delivery device 30 embodiments begin operation by having electronics 46 programmed to operate the permanent solenoid pump 48 to deliver therapeutic substance 36 at a programmed rate. The therapeutic substance 36 is supplied from a therapeutic substance reservoir 42 to a therapeutic substance inlet 76. The solenoid pump 48 generally operates by retracting a pump piston 58 and then actuating the pump piston 58 while operating valves to deliver therapeutic substance 36 through an infusion outlet 54 at a programmed rate. This operation is repeated a predetermined number of times at predetermined intervals to delivery therapeutic substance 36 at the programmed rate. For example, a solenoid pump 48 with a stroke volume of 2.0 micro liters would typically be operated from a maximum of about 10 cycles per second (Hz) to achieve an infusion rate of 1.2 milliliters per minute to a minimum of about 1.0 cycle per hour to achieve an infusion rate of about 48 micro liters per day.

Retracting the pump piston 58 is initiated when a first coil 68 for current flow in a first direction is energized 112 and a second coil 70 for current flow in an opposite direction are energized 112 to create a electromagnetic axial force. The pump piston 58 is retracted 114 when the electromagnetic axial forces acts on a permanent magnet 66 carried on the pump piston 58. While the pump piston 58 is retracting, an inlet valve 62 is opened 116 and a biasing element 60 is loaded. A pump chamber 88 is filled with therapeutic substance 36 through the inlet valve 62 while the pump piston 58 is being retracted 114. In an embodiment having a piston seal 78, during pump piston 58 retraction the piston seal 78 can also be configured to dampen the shock when the pump piston 58 reaches its fully retracted position. By dampening this shock, the piston seal 78 can reduce some wear and noise that occurs when the pump piston 58 reaches its fully retracted position. In embodiments having an anti-cavitation valve 90, the anti-cavitation valve 90 prevents therapeutic substance 36 in the inlet chamber 86 from flowing back to the therapeutic substance reservoir 42 when the pump piston 58 retracts. The anti-cavitation valve 90 helps maintain higher pump chamber 88 pressures during pump piston 58 retraction, which makes it easier to pass air bubbles.

During pump piston 58 retraction assuming there is anti-cavitation valve 90 and both the inlet chamber 86 and pump chamber 88 are filled with therapeutic substance 36, the pressure in the inlet chamber 86 will increase rapidly due to the incompressibility of liquids which will cause the therapeutic substance 36 to flow through the piston fluid path 84 into the pump chamber 88 without causing the pump chamber 88 pressure to decrease to the level that would cause gasses to come out of solution. After the pump piston 58 is retracted, operation of the solenoid pump 48 continues when the pump piston 58 is actuated.

Actuating the pump piston is initiated when the first coil 68 for current flow in the first direction is de-energized 122, and the second coil 70 for current flow in the opposite direction is de-energized 122 to collapse the electromagnetic axial force. As the electromagnetic axial force collapses, the biasing element 60 is unloaded, and the pump piston 58 is actuated by the biasing element 60 driving the pump piston 58 toward the outlet enclosure 74. While the pump piston 58 is being actuated 126, pressure generated in the pumping chamber 88 opens the outlet valve 64. The open outlet valve 64 permits a

stroke volume to be expelled through the infusion outlet 54 while the pump piston 58 is actuated 126. The therapeutic substance 36 discharged through the infusion outlet 54 is delivered at a programmed rate. In some embodiments during pump piston actuation 126, the piston seal 78 substantially prevents therapeutic substance 36 from flowing around the pump piston 58 back into the inlet chamber 86. The previously discussed method embodiment elements are presented in a general sequence that is intended to be limiting only when a particular element is required to be sequence in a certain way for the entire method embodiment to be practical. Pump piston actuation 126 can be mathematically characterized.

During piston actuation 126 to expulse therapeutic substance 36, when the pump chamber 88 volume is decreasing and the inlet chamber 86 volume is increasing the following relationships exist. The final pressure in the pump chamber 88 can be express as $P_{pc\ final} = \frac{P_{pc\ initial}}{CR_{pc}}$ (Equation 3) where $P_{pc\ final}$ is the final pressure in the pump chamber 88, $P_{pc\ initial}$ is the initial pressure in the pump chamber 88, and CR_{pc} is the compression ratio in the pump chamber 88. The final pressure in the inlet chamber 86 can be expressed as $P_{ic\ final} = \frac{P_{ic\ initial}}{CR_{ic}}$ (Equation 4) where $P_{ic\ final}$ is the final pressure in the inlet chamber 86, $P_{ic\ initial}$ is the initial pressure in the inlet chamber 86, and CR_{ic} is the compression ratio in the pump chamber 88. Therapeutic substance 36 flows through the outlet valve 64 when $P_{pc\ final} \geq P_a + P_{ovc}$ (Equation 5) where P_{ic} is the initial pressure in the inlet chamber 86, P_a is the ambient pressure at the pump outlet, and P_{ovc} is outlet valve 64 cracking (opening) pressure. The above relationships assume that there is an anti-cavitation valve 90, there is no air in the pump chamber 88, and since liquids are essential incompressible P_{ic} decreases as the pump piston 58 is actuated.

Thus, embodiments of the solenoid pump 48 are disclosed to increase energy efficiency, increase accuracy, reduce the residential space requirement, improve therapeutic substance compatibility, and provide many other improvements. One skilled in the art will appreciate that the present invention can be practiced with embodiments other than those disclosed. The disclosed embodiments are presented for purposes of

illustration and not limitation, and the present invention is limited only by the claims that follow.

What is claimed is:

1. An implantable therapeutic substance delivery device having a permanent magnet solenoid pump, comprising:
a housing;
5 a therapeutic substance reservoir coupled to the housing, the therapeutic substance reservoir having a reservoir outlet;
a power source carried in the housing;
electronics carried in the housing and coupled to the power source; and,
a permanent magnet solenoid pump coupled to the electronics and coupled to the
10 reservoir outlet, the permanent magnet solenoid pump configured for pumping a therapeutic substance from the therapeutic substance reservoir through an infusion outlet at a programmed rate.
2. The implantable therapeutic substance delivery device as in claim 1 wherein a therapeutic substance flow path through the permanent magnet solenoid pump is
15 composed of a therapeutic substance compatible material.
3. The implantable therapeutic substance delivery device as in claim 1 wherein the permanent magnetic solenoid pump, further comprises
a pump cylinder having an inlet enclosure and an outlet enclosure, the inlet
20 enclosure having a therapeutic substance inlet coupled to the reservoir outlet, and the outlet enclosure having an infusion outlet;
a pump piston moveable within the pump cylinder, the pump piston having a piston fluid path, a piston inlet end and a piston outlet end, the pump piston forming an inlet chamber between the pump piston and the inlet enclosure
and a pumping chamber between the pump piston and the outlet enclosure,
25 and at least one biasing element positioned between the pump piston and the inlet enclosure;
an inlet valve carried on the pump piston in operating relation to the piston fluid path, the inlet valve configured to control the flow of the therapeutic substance into the pump chamber;

an outlet valve carried on the outlet enclosure, the outlet valve configured to control the flow of therapeutic substance from the pumping chamber into the infusion outlet;

at least a first permanent magnet carried on the pump piston, the first permanent magnet having a first pole and a second pole;

at least a first coil formed around the pump cylinder positioned adjacent to the first pole of the first permanent magnet; and,

at least a second coil formed around the pump cylinder positioned adjacent to the second pole of first the permanent magnet.

4. The implantable therapeutic substance delivery device as in claim 3, further comprising a third coil formed around the pump cylinder, the third coil configured for current to flow in the opposite direction from current flow in an adjacent first coil or second coil, and a second permanent magnet carried on the pump piston, the second permanent magnet and the first permanent magnet having like poles adjacent.

5. The implantable therapeutic substance delivery device as in claim 3, further comprising N coils formed around the pump cylinder and N-1 permanent magnets carried on the pump piston where N is an integer in the range from about 3 to 10.

6. The implantable therapeutic substance delivery device as in claim 3 wherein the biasing element exerts force on the pump piston to expel fluid through the infusion outlet.

7. The implantable therapeutic substance delivery device as in claim 6 wherein the biasing element exerts substantially the sole force on the pump piston to expel therapeutic substance through the infusion outlet.

8. The implantable therapeutic substance delivery device as in claim 3 wherein the biasing element provides force to seal the inlet valve against the outlet enclosure to provide redundant protection against unintended therapeutic substance infusion.

9. The implantable therapeutic substance delivery device as in claim 1 wherein the therapeutic substance reservoir coupled to the housing is a separate therapeutic substance reservoir.

10. The implantable therapeutic substance delivery device as in claim 1 wherein the permanent magnet solenoid pump consumes less than about 3 Joules per milliliter at about 137,895 Pascals back pressure.
11. The implantable therapeutic substance delivery device as in claim 1 wherein the permanent magnetic solenoid pump is about 5% to about 10% efficient in terms of electrical energy input and fluid work output.
12. The implantable therapeutic substance delivery device as in claim 1 wherein the permanent magnet solenoid pump occupies a total volume of less than about 0.5 cubic centimeters.
13. An implantable therapeutic substance delivery device with a permanent magnet solenoid pump, comprising:
 - a housing;
 - a therapeutic substance reservoir coupled to the housing, the therapeutic substance reservoir having a reservoir outlet;
 - a power source carried in the housing;
 - electronics carried in the housing and coupled to the power source; and,
 - means for pumping coupled to the electronics and coupled to the reservoir outlet, the means for pumping configured to pump a therapeutic substance from the therapeutic substance reservoir through an infusion outlet at a programmed rate.
14. A permanent magnet solenoid pump for an implantable medical device, comprising
 - a pump cylinder having an inlet enclosure and an outlet enclosure;
 - an therapeutic substance inlet coupled to the therapeutic substance reservoir and coupled to inlet enclosure;
 - an infusion outlet coupled to the outlet enclosure;
 - a pump piston moveable within the pump cylinder, the pump piston having a piston fluid path, a piston inlet end and a piston outlet end, the pump piston forming an inlet chamber between the pump piston and the inlet enclosure and a pumping chamber between the pump piston and the outlet enclosure, and at least one biasing element positioned between the pump piston and the inlet enclosure;

an inlet valve carried on a pump piston outlet end;
an outlet valve carried in the outlet enclosure and coupled to the infusion outlet;
at least a first permanent magnet carried on the pump piston, the first permanent
magnet having a first pole and a second pole;
5 at least a first coil configured around the pump cylinder, the first coil positioned
adjacent to the first pole of the first permanent magnet; and,
at least a second coil configured around the pump cylinder, the second coil
positioned adjacent to the second pole of the first permanent magnet.

- 10 15. The implantable therapeutic substance delivery device as in claim 14, further
comprising a third coil formed around the pump cylinder, the third coil configured
for current to flow in the opposite direction from current flow in an adjacent first
coil or second coil, and a second permanent magnet carried on the pump piston, the
second permanent magnet and the first permanent magnet having like poles
adjacent.
- 15 16. The implantable therapeutic substance delivery device as in claim 14, further
comprising N coils formed around the pump cylinder and N-1 permanent magnets
carried on the pump piston where N is an integer in the range from about 3 to 10.
17. The implantable therapeutic substance delivery device as in claim 14 wherein
adjacent coils are configured for current flow in opposite directions.
- 20 18. The implantable therapeutic substance delivery device as in claim 14 wherein the
first coil and the second coil are energized for pump piston movement toward the
inlet enclosure to fill the pump chamber from the inlet chamber.
19. The implantable therapeutic substance delivery device as in claim 14 wherein the
biasing element exerts force on the pump piston to expulse therapeutic substance
25 through the infusion outlet.
20. The implantable therapeutic substance delivery device as in claim 19 wherein the
biasing element exerts substantially the sole force on the pump piston to expel fluid
through the infusion outlet.
- 30 21. The implantable therapeutic substance delivery device as in claim 14 wherein the
biasing element provides force to seal the inlet valve against the outlet enclosure to
provide redundant protection against unintended therapeutic substance infusion.

22. The implantable therapeutic substance delivery device as in claim 14 wherein the biasing element is at least one spring.
23. The implantable therapeutic substance delivery device as in claim 22 wherein the biasing element is at least one coil spring.
- 5 24. The implantable therapeutic substance delivery device as in claim 14 further comprising a magnetically permeable yoke placed around at least the first coil and the second coil to improve magnetic efficiency.
25. The implantable therapeutic substance delivery device as in claim 24 wherein the magnetically permeable yoke shields at least a permanent magnet from external high magnetic fields to protect the permanent magnet from demagnetization.
- 10 26. The implantable therapeutic substance delivery device as in claim 25 wherein the external high magnetic field is created by equipment selected from the group consisting of Magnetic Resonance Imaging (MRI) equipment and magnetic security equipment.
- 15 27. The implantable therapeutic substance delivery device as in claim 14 further comprising at least a first pole piece carried on the pump piston.
28. The implantable therapeutic substance delivery device as in claim 27 wherein the first pole piece is positioned between the permanent magnet and the piston inlet end to improve magnetic efficiency.
- 20 29. The implantable therapeutic substance delivery device as in claim 27 further comprising at least a second pole piece carried on the pump piston.
30. The implantable therapeutic substance delivery device as in claim 29 wherein the second pole piece is positioned between the permanent magnet and the piston outlet end to improve magnetic efficiency.
- 25 31. The implantable therapeutic substance delivery device as in claim 29 further comprising at least a third pole piece carried on the pump piston.
32. The implantable therapeutic substance delivery device as in claim 31 wherein the third pole piece is positioned between a first permanent magnet and a second permanent magnet to improve magnetic efficiency.

33. The implantable therapeutic substance delivery device as in claim 14 wherein a therapeutic substance flow path through the permanent magnet solenoid pump is composed of a therapeutic substance compatible material.
34. The implantable therapeutic substance delivery device as in claim 33 wherein the
5 therapeutic substance compatible material is selected from the group consisting of titanium, tantalum, stainless steel, and plastic.
35. The implantable therapeutic substance delivery device as in claim 33 wherein the therapeutic substance compatible material is also biocompatible.
36. The implantable therapeutic substance delivery device as in claim 14 wherein the
10 inlet valve is selected from the group consisting of a flapper valve, an annular flapper valve, a ball valve, a reed valve, a duckbill valve, and a poppet valve.
37. The implantable therapeutic substance delivery device as in claim 14, wherein the outlet valve is selected from the group consisting of a flapper valve, a ball valve, a reed valve, a duckbill valve, and a poppet valve.
38. The implantable therapeutic substance delivery device as in claim 14, further
15 comprising a anti-cavitation valve position in fluid communication with the therapeutic substance inlet.
39. The implantable therapeutic substance delivery device as in claim 38, wherein the anti-cavitation valve is selected from the group consisting of a flapper valve, an
20 annular flapper valve, a ball valve, a reed valve, a duckbill valve, and a poppet valve.
40. The implantable therapeutic substance delivery device as in claim 14, further comprising a piston seal positioned between the pump piston and the pump cylinder
41. The implantable therapeutic substance delivery device as in claim 14 wherein the
25 pump piston is coated with a flouroplastic to reduce wear.
42. The implantable therapeutic substance delivery device as in claim 14 wherein the permanent magnet material is selected from the group consisting of samarium cobalt, neodymium, ceramic, and alnico.

43. The implantable therapeutic substance delivery device as in claim 14 wherein when the pump piston is fully positioned toward the inlet enclosure there is a maximum pump chamber volume.
- 5 44. The implantable therapeutic substance delivery device as in claim 14 wherein the pumping chamber has a pump chamber volume comprising a stroke volume and a dead volume.
45. The implantable therapeutic substance delivery device as in claim 44 wherein the stroke volume is in the range from about 0.5 micro liters to about 5 micro liters.
- 10 46. The implantable therapeutic substance delivery device as in claim 44 wherein the dead volume is less than half the stroke volume.
47. The implantable therapeutic substance delivery device as in claim 14 wherein the sum of an inlet valve opening pressure and an outlet valve opening pressure exceeds the maximum pressure of the reservoir less an infusion site pressure to protect against unintended therapeutic substance infusion.
- 15 48. A permanent magnet solenoid pump for an implantable medical device, comprising a pump cylinder having an inlet enclosure and an outlet enclosure;
a therapeutic substance inlet coupled to the therapeutic substance reservoir and coupled to the inlet enclosure;
an infusion outlet coupled to the outlet enclosure;
20 a means for pumping to pump therapeutic substance from the therapeutic substance reservoir through an infusion outlet at a programmed rate, the means for pumping having a pump piston, a pump chamber, and a biasing element;
a means for inlet valving to control therapeutic substance flow into the pump chamber;
25 a means for outlet valving to control therapeutic substance flow out of the pump chamber;
a means for creating at least a first permanent magnet field carried on the pump piston to impart a magnetic potential to the pump piston;
a means for creating at least a first electromagnetic field around the pump cylinder
30 to act upon the means for creating a permanent magnetic field to impart movement to the pump piston; and,

a means for creating at least a second electromagnetic field around the pump cylinder to act upon the means for creating a permanent magnetic field to impart movement to the pump piston.

49. The permanent magnet solenoid pump for an implantable therapeutic substance delivery device as in claim 48, further comprising a means for creating a third
5 electromagnetic field around the pump cylinder to act upon a means for creating a second permanent magnetic field carried on the pump piston to impart movement to the pump piston.

50. The implantable therapeutic substance delivery device as in claim 48, further
10 comprising means for creating N magnetic fields around the pump cylinder to act upon a means for creating N-1 permanent magnetic fields carried on the pump piston to impart movement to the pump piston where N is an integer in the range from about 3 to 10.

51. A method for operating an implantable therapeutic substance delivery device
15 having a permanent magnet solenoid pump, comprising:
programming electronics to infuse therapeutic substance supplied by the
therapeutic substance reservoir at a programmed infusion rate;
supplying therapeutic substance from a therapeutic substance reservoir to a
therapeutic substance inlet;
20 retracting a pump piston by energizing at least a first coil and at least a second coil
to create an electromagnetic axial force to act on at least one permanent
magnet carried on the pump piston;
opening an inlet valve while the pump piston is retracting;
loading at least one biasing element while the pump piston is retracting;
25 filling a pump chamber with therapeutic substance from the therapeutic substance
inlet while the piston is retracting and the inlet valve is open;
actuating the pump piston by de-energizing the first coil and the second coil to
collapse the electromagnetic axial force to release the permanent magnet
carried on the pump piston while the biasing element unloads;
30 opening an outlet valve while the pump piston is actuating;

expulsing a stroke volume through the open outlet valve while the pump piston is actuating; and,
delivering therapeutic substance from the open outlet valve through an infusion outlet at the programmed infusion rate.

- 5 52. The method as in claim 51, further comprising sealing the inlet valve when the pump piston is fully actuated to provide redundant protection against unintended therapeutic substance delivery to a patient.
- 10 53. The method as in claim 51 wherein there at N coils configured around the pump cylinder and N-1 permanent magnets carried on the pump piston where N is an integer in the range from about 3 to 10.
- 15 54. A method for operating a permanent magnet solenoid pump in an implantable therapeutic substance delivery device, comprising:
energizing at least a first coil for current flow in a first direction and energizing at least a second coil for current flow in an opposite direction to create an electromagnetic axial force;
retracting a pump piston with the electromagnetic axial force acting on at least one permanent magnet carried on the pump piston;
opening an inlet valve while the pump piston is retracting;
loading at least one biasing element while the pump piston is retracting;
20 filling a pump chamber with therapeutic substance from the therapeutic substance inlet while the piston is retracting and the inlet valve is open;
de-energizing the first coil for current flow in a first direction and de-energizing the second coil for current flow in the opposite direction to collapse the electromagnetic axial force;
25 unloading the biasing element;
actuating the pump piston while the biasing element unloads;
opening an outlet valve while the pump piston is actuating; and,
expulsing a stroke volume through the open outlet valve while the pump piston is actuating.

55. The method as in claim 54, further comprising sealing the inlet valve when the pump piston is fully actuated to reduce the opportunity for unintended therapeutic substance delivery to a patient.
56. The method as in claim 54 wherein there are N coils configured around the pump cylinder and N-1 permanent magnets carried on the pump piston where N is an integer in the range from about 3 to 10.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14a




FIG. 14b




FIG. 15




FIG. 16




FIG. 17
Two Coils and One Magnet




FIG. 18




FIG. 19

Three Coils and Two Magnets

19/19




FIG. 20

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 October 2002 (24.10.2002)

PCT

(10) International Publication Number
WO 02/083208 A3

(51) International Patent Classification⁷: **A61M 5/142**

(21) International Application Number: **PCT/US01/44438**

(22) International Filing Date:
27 November 2001 (27.11.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/282,775 10 April 2001 (10.04.2001) US

(71) Applicant: **MEDTRONIC, INC.** [US/US]; 710
Medtronic Parkway NE, Minneapolis, MN 55432 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report


(72) Inventor: **OLSEN, James, M.**; 10380 51st Place North,
Plymouth, MN 55442 (US).

(88) Date of publication of the international search report:
10 April 2003

(74) Agents: **WALDKOETTER, Eric, R.** et al.; Medtronic,
Inc. LC340, 710 Medtronic Parkway NE, Minneapolis,
MN 55432 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **IMPLANTABLE THERAPEUTIC SUBSTANCE DELIVERY DEVICE HAVING A PERMANENT MAGNET SOLENOID PUMP**



WO 02/083208 A3

(57) Abstract: A medical device known as an implantable therapeutic substance delivery device is configured for implanting in humans to deliver a therapeutic substance such as pharmaceutical compositions, genetic materials, and biologics to treat a variety of medical conditions such as pain, spasticity, cancer, and many other conditions. The therapeutic substance delivery device has a permanent magnet solenoid pump that is energy efficient, accurate, small, compatible with therapeutic substances, and has many other improvements. The implantable therapeutic substance delivery device has a housing, a therapeutic substance reservoir, a power source, electronics, and a permanent magnet solenoid pump. The therapeutic substance reservoir is configured to contain a therapeutic substance and is coupled to the housing. The power source is carried in the housing to power the electronics and solenoid pump. The electronics are coupled to the solenoid pump and the solenoid pump is coupled to the therapeutic substance reservoir. The permanent magnet solenoid pump is configured for pumping therapeutic substance from the therapeutic substance reservoir through an infusion outlet at a programmed infusion rate. Many embodiments of the permanent magnet solenoid pump and its methods of operation are possible.

INTERNATIONAL SEARCH REPORT

Internat Application No

PCT/US 01/44438

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 A61M5/142

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI, Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 437 815 A (MCMULLEN JOHN K) 20 March 1984 (1984-03-20) the whole document	1-50
A	US 5 462 525 A (SRISATHAPAT CHAD ET AL) 31 October 1995 (1995-10-31) abstract	1,13,14, 48
A	CH 657 275 A (SULZER AG) 29 August 1986 (1986-08-29) abstract; figure 2	1,13,14, 48
A	EP 0 605 903 A (TDK CORP) 13 July 1994 (1994-07-13) abstract; figures 2,3	1,13,14, 48
	--- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

4 December 2002

Date of mailing of the international search report

12/12/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Nielsen, M

INTERNATIONAL SEARCH REPORT

Interna

Application No

PCT/US 01/44438

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 102 610 A (TABOADA JOHN ET AL) 25 July 1978 (1978-07-25) abstract -----	1, 13, 14, 48

INTERNATIONAL SEARCH REPORT

Int'l application No.
PCT/US 01/44438

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 51-56
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by therapy
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

nation on patent family members

Internat Application No

PCT/US 01/44438

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4437815	A	20-03-1984	AU 542730 B2	07-03-1985
			AU 6339580 A	14-04-1981
			DE 3070387 D1	02-05-1985
			DK 231881 A	27-05-1981
			EP 0037400 A1	14-10-1981
			WO 8100888 A1	02-04-1981
			JP 56501289 T	10-09-1981
			NO 811779 A ,B,	26-05-1981
US 5462525	A	31-10-1995	CA 2151705 A1	15-12-1995
			EP 0687476 A2	20-12-1995
			JP 8054267 A	27-02-1996
CH 657275	A	29-08-1986	CH 657275 A5	29-08-1986
EP 0605903	A	13-07-1994	JP 6200869 A	19-07-1994
			JP 6346833 A	20-12-1994
			DE 69311525 D1	17-07-1997
			DE 69311525 T2	02-10-1997
			EP 0605903 A1	13-07-1994
			US 5472323 A	05-12-1995
US 4102610	A	25-07-1978	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.